MAGMA







12x24 18x18 13: 18x36, 2x2 Basketweave, 1x12 Mosaic and 3x12 Sbn also available







12x24 18x18 13x13 18x36, 2x2 Basketweave, 1x12 Mosaic and 3x12 Sbn also available







12x24 18x36, 2x2 Basketweave, 1x12 Mosaic and 3x12 Sbn also available







1x12 Mosaic set on 12x12 mesh sheet

2x2 Basketweave set on 13x13 mesh sheet

Gold 5x5	Gold 5x5
Moderno	Classico
assortment	assortment
7676	6)X 62 (6)X
6,60,60	



Moderno assortmen Classico assortment

	VALUE	STANDARD
Abrasion resistance	Beige PEI 4 Copper PEI 4 Charcoal PEI 3	GLAZED ISO 10545-7
Water absorption	Eb ≤% 0,3	ISO 10545-3
Breaking strength	12x24: ≥ 1500 N 13x13: ≥ 1500 N 18x18: ≥ 1500 N 18x36: ≥ 2500 N	ISO 10545-4
Scratch hardness	8 Mohs	EN 101
Chemical resistance	GA	ISO 10545-13
Stain resistance	A/5	ISO 10545-14
Resistance to frost	resistant- no alternation with 100 cycles	ISO 10545-12
Thermal shock resistance	resistant	ISO 10545-9
Crazing resistance	resistant	ISO 10545-11
Color shade variation	V2	CTDA
Coefficients of friction	Wet DCOF: 0,60-0,65 Dry DCOF: 0,63-0,68	ANSI / NFSI B137.1-2012

Tile Applicat	tions:		
Usage	Residential	Light Commercial	Commercial
Floors	•	•	•
Walls	•	•	•
Countertops			

Variations in shade and color and sometimes texture, are inherent in all tile products such as porcelain, glass and ceramic. This variation can be present from piece to piece within any production run, Prior to any installation, several loose tiles should be arranged and approved by the customer.

